

BOLLARDS

PROCITY®

RETRACTABLE BOLLARDS

TECHNICAL CHARACTERISTICS

- > Bollards in cast iron (except Barcelona)
- > Supplied with full installation and maintenance instructions which must be carefully followed to ensure correct functioning and lifespan
- > Applied force of 20kg is required to retract the bollard

Operating

- > Closing: with one turn of the key, the bollard rises and automatically locks into the raised position
- > Opening: turn the key and remove it, then apply vertical pressure to the dome of the bollard with the foot, until it locks automatically in the lowered position
- > Lock unit: made of stainless steel. The stainless steel lock protector is spring loaded and shields the mechanism from ingress of dirt. The standard lock supplied uses an 11 mm triangle key

Ground-cover (skirt)

- > Made of Ø 460, 10 mm gauge steel
- > Non-slip with a raised paved effect and a slope calculated to allow water to run off
- > Galvanised & lacquered black. Fixed to the casing by four stainless steel Hex socket cap head screws (Ø 12 mm)

Sliding mechanism

- > The bollard support is equipped with guide ball bearings, distortion resistant, hard wearing. The bollard slides vertically in a removable drum inserted in the external casing and is raised using a sealed gas piston

Casing

- > External casing made of galvanised sheet steel, with strong lifting eyelets for quick and easy installation
- > Ht 1030 x 545 mm



RECOMMENDATION

Retractable bollards must not be placed in the tyre paths of vehicles as this will shorten the lifespan of the product.



INSTALLATION

- > To be concreted directly into the ground



PRODUCT CODES AND SIZES

| | | | | | | |
|--------------------------------|--------------------------------|---------------------------------|---------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| | | | | | | |
| City HAG 555 mm Ø 160 mm | City HAG 680 mm Ø 160 mm | Agora HAG 590 mm Ø 270 mm | Agora HAG 725 mm Ø 160 mm | Barcelona HAG 515 mm Ø 273 mm | Barcelona HAG 605 mm Ø 219 mm | Barcelona HAG 705 mm Ø 160 mm |
| 206572 | 206616 | 206617 | 206618 | 206611 | 206612 | 206613 |



FINISH

- > Painted after zinc anti-corrosion treatment in our RAL colours

Our standard colours

