

SB.22 Speed Ramp

(50MM HIGH AND 75MM HIGH)

SAFETY

We recommend the following minimum precautions are taken:

Wear appropriate safety clothing.

Eye protection and hand protection should be worn, including safety helmet.

Wear strong protective gloves.

Secure the site from pedestrians and vehicles, where applicable, by the use of high visibility tape, barriers, cones, safety lamps etc.

If you use a power supply ensure that it is secure and in a safe dry location.

Ensure there are no underground services that may be affected.

A minimum of two personnel are recommended.

FEATURES

For use in private car parks and access roads to slow the speed of traffic.

The recycled PVC speed ramps are available in two heights; 50mm which is designed to slow the speed of traffic to 10 mph, and 75mm which slows the speed of traffic to 5 mph. The speed ramps can be used in any size roadway due to their modular system.

It is recommended that warning signs are installed to advise drivers accordingly.

INSTALLATION INSTRUCTIONS

If the surface is poor quality, concrete will need to be laid to a depth of 150mm.

Determine the position of the installation. Ensure there is an adequate gap at the gutter to permit satisfactory drainage during rain fall, and for easier cycling access.

Lay the speed ramp in position and as you place each piece place the dog-bone fixing under the ramp.

Leave the speed ramp in position and (starting from the middle) drill with a 12mm bit through the fixing holes.

Use a pump to blow out any dust from the holes (a bicycle pump will do).

Insert the plug (with bolt partway in) and bolt into position.

MAINTENANCE

Occasionally check that all fixing bolts are suitably tight and have not worked loose.