

PRODUCT SPECIFICATION

MATERIAL:
C30 Concrete

FINISH:
Smooth Grey

WEIGHT:
102 KG Approx

MAINTENANCE:
MSFCM-CND1 - Concrete Cleaning and Maintenance

INSTALLATION:

1. Excavate suitable foundation for the bollard
2. Position bollard in excavated hole.
3. Cast concrete mass around bollard
4. Allow the foundation to cure

NOTES:

All dimensions are in millimeters unless otherwise stated

This drawing is the sole property and copyright of Marshalls Street Furniture and may not be disclosed to any third party or reproduced in whole or in part without the prior written consent of an authorised representative of the company.


Marshalls PLC reserves the right to change the specifications of products noted above without notice

Foundation sizes given are suited to sub-soils with good load bearing capabilities, where adverse site conditions are met professional advice to be sought

RevNo	Revision Note	Date	Signature
A	FIRST ISSUE	05/07/11	CJW

Title:
CONCRETE BOLLARD TYPE 1

Drawing No: PS-BA-BL-00005



THIRD ANGLE PROJECTION

Basics
P.O. Box 6, High Flankworth,
Tyne Tunnel Trading Estate,
North Shields,
Tyne and Wear,
NE29 7SU
Tel: (0870) 600 2425
Fax: (0191) 258 8040

Drawn By: CJW Date: 17/03/11

DO NOT SCALE DRAWING
Scale: NTS Sheet: 1 of 1 **A3**

